

HALOLINE ECO 80 W 230 V R7S

HALOLINE ECO | Double ended halogen lamps with tube base



- General illumination
- Entrance lighting
- Pathway lighting
- · Garden lighting
- Traffic areas
- Shops
- · Restaurants, hotels and similar prestigious applications
- · Offices, public buildings

Product benefits

- · Brilliant ECO accent lighting
- Direct replacement for standard tubular halogen lamps
- Significantly lower CO₂ emissions
- Lower thermal output (compared with the standard reference product)
- · No transformer required
- · Contains no mercury, can be thrown away with normal household waste

Product features

• Average life: 2,000 h

Dimmable

• Color rendering index R_a: 100

• Base: R7s



Technical data

Electrical data

Rated wattage	80 W
Nominal wattage	80 W
Nominal voltage	230 V

Light technical data

Light color as per EN 12464-1	Warm White
Nominal luminous flux	1400 lm
Rated luminous flux	1400 lm
Color temperature	2950 K
Color rendering index Ra	100
Starting time	0.0 s
Warm-up time (60 %)	0 s

Dimensions & weight

Length	80.3 mm
Overall length	74.9 mm
Diameter	12.0 mm
Outer bulb	T12





Product line drawing with letters

Colors & materials

Lamp mercury content	0.0 mg
Mercury-free	Yes

Lifespan

Nominal lamp life time	2000 h
Rated lamp life time	2000 h

Additional product data

Base (standard designation)	R7s
Footnote used only for product	Fuse protection with indicated values recommended acc. to IEC60357, EN60357/For outdoor applications and operation in damp locations special approved fixtures are required

Product datasheet



Capabilities

Dimmable	Yes
Burning position	Any
Fuse, quick-acting	2.0 A

Certificates & standards

EEI – Energy Label	С
--------------------	---

Country specific categorizations

ILCOS	HDG-80-230-R7s-74,9
Order reference	64690 ECO



Logistical Data

Product code	Packaging unit (Pieces/Unit)	Dimensions (height x width x length)	Gross weight	Volume
4008321928078	Folding carton box 1	21 mm x 18 mm x 87 mm	6.00 g	0.03 dm³
4008321327758	Shipping carton box 20	92 mm x 77 mm x 112 mm	209.00 g	0.79 dm³

Product datasheet



Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.